Doc : SPEC-0278

Version : 01 Page : 1 of 3



Product Specifications

Brand : Klinion® Protection

Product : Particle Filtering mask type FFP2

Packaging & Product Reference

Product		Mask size		Piece(s)	Carton	Pieces	Carton
Reference	Description	in CM	Colour	per Inner	dimension in	per Outer	dimension in
Reference		IN CIM		carton	MM	Carton	MM
552710 /	KPP FACE MASK FFP2	23*12	White	10	140*121*40	1200	510*435*440
KF-A F10(SC)	EARLOOPS WHITE	25 12					

^{*} Sizes are approximate

Product description

Klinion FFP2 particle filtering half masks is a white 5 layer filtration mask and consists of PP nonwoven fabric, PP melt-blown fabric, spunlaced nonwoven fabric, nose clip, ear loops and hook.

Intended use

This product, which is normally used in the general working environment, is designed to provide reliable respiratory protection and against certain airborne particles and dust, block body fluids and so on.

Classification

PPE Regulation (EU) 2016/425 Category III

Features

- Premium materials ensure mask will not lint or tear.
- Elastic and comfortable ear-loops.
- It can be used with S-shaped hook for more comfortable wearing.
- Conformable nose clamp to reduce air leakage.
- Specially designed inner facing improves comfort.
- Flexible & foldable design for extra comfort and easy storage.
- Thin & light multi-layer design reducing respiratory resistance.



Doc : SPEC-0278

Version : 01 Page : 2 of 3



Product Specifications

Performance and Limitation of Use

The mask must be selected properly for intended application. An individual risk assessment must be evaluated. Check the mask that it is undamaged with no visible defects. Do not use the mask if a defect is present or the end of shelf life has been exceeded.

In compliance with: EN149:2001+A1:2009, FFP2

Product performance				
Test item	Performance requirement			
PFE @ 0.1 microns	≥ 94%			
Total inward leakage (TIL) by individual wearer arithmetic means	< 8%			
BR inhalation 30I/min	< 70 Pa/cm2			
BR inhalation 95I/min	< 240 Pa/cm2			
BR exhalation 160I/min	< 300 Pa/cm2			
Flame spread	≤ 5S			
CO2 Clearance	< 1%			

Directions for use

- 1. Put the mask on face with the nose clip on the bridge of nose.
- 2. Position ear loops behind the head. Use hook to tighten ear loops to ensure a good seal.
- 3. Extend the mask to cover mouth and chin. Mold nose clip to fit the shape of nose.
- 4. To check fit, cup both hands over the mask and exhale vigorously. If air flows around nose, tighten the nose clip. If air leaks around the edge, reposition the ear loops for better fit. Recheck the seal and repeat the procedure until the mask is sealed properly.

Product components

Outer layer	Polypropylene nonwoven (White)		
Middle layer 1	Melt blown Polypropylene (White)		
Middle layer 2	Melt blown Polypropylene (White)		
Middle layer 3	Spun laced nonwoven (White)		
Inner layer	Polypropylene nonwoven (White)		



Doc : SPEC-0278

Version : 01 Page : 3 of 3



Product Specifications

- Products listed on this specification are:
 - o Latex-free
 - o Nose piece is nickel-free
 - o Absent of human or animal tissue, blood or blood derivative

Sterilization

Not applicable. This product is provided non-sterile

Storage conditions

It is recommended to store protected from direct sunlight in a clean, dry space at ambient temperature.

Shelf life

2 years

Pictures





Approval	Name	Date	Signature
Product Manager	Levine van Buren	02-08-2022	ARANA
RA-Coordinator	Warsha Baboelal	02-08-2022	(Lipsipping)

